

Outline


- Focus is the inspection of <20' span structures
 - MiSIM Chapter 12
- Three main counties GLEG performs inspections for
 - Washtenaw County Road Commission
 - Bay County Road Commission
 - Road Commission of Oakland County
- Discuss how the process differs between counties
 - Inspection process
 - Reporting process
 - Naming convention of culverts
 - Replacement process
- Q&A



GREAT LAKES ENGINEERING GROUP

County Culvert Inspections

**MiSIM Chapter 12 deals
with non-NBI
Structures**



GREAT LAKES ENGINEERING GROUP

Washtenaw County Road Commission


- County has roughly 2,500 culverts in the inventory
 - 79% of inventory has 4' span or less
 - 21% of inventory has span that ranges from 5' to 20'
 - GLEG focuses on inspecting the culverts that range from 5' to 20'
- Inventory mainly consists of concrete and steel
- Washtenaw has inspection structures less than 20' long for over 25 years
- Significantly expanded culvert inspection program around 6 years ago



GREAT LAKES ENGINEERING GROUP


Washtenaw County (<20' Inspection)

- County has 20 townships
- Inspection process:
 - County has four rows (tiers) of townships. Each row (tier) is five townships wide
 - Every year, a different tier of townships is inspected
 - For example – Tier 1 is inspected in 2021, Tier 2 is inspected in 2022, Tier 3 is inspected in 2023, and Tier 4 is inspected in 2024



GREAT LAKES ENGINEERING GROUP

- Inspection process:
 - In addition to the tier system, every culvert that is rated a 3 or less (serious condition and worse) is inspected every two years
- Roadsoft Laptop Data Collector used as primary source for culvert inventory
 - Every year GLEG receives a Roadsoft file from the County with the assigned inspections for the year
 - Roadsoft file contains the culvert location and general information



- Culvert reporting process:
 - All comments and ratings are entered into an Excel template that was created by GLEG
 - GLEG created a separate template for culverts and bridges

[illegible]

Washtenaw County (<20' Inspection)

- Culvert reporting process
 - All typical photos and additional deterioration photos are entered into a photo log template that was created by GLEG and a PDF is created
 - After all the inspection reports and photo logs are created, they are uploaded into the Roadsoft file that is provided by the county
 - As well as uploading the inspection report and photo log, the rating for the culvert and the channel are updated within the Roadsoft file



GREAT LAKES ENGINEERING GROUP

Washtenaw County (<20' Inspection)

- Culvert reporting process
 - Any significant changes or safety concerns are handled with an email/call to the county
 - All posting changes were included in a summary spreadsheet that was sent to the county at the end of all the inspections



Facility	Feature	Structure Number	Township	Date	Culvert Rating	Current Posting	New Posting
N Parker Rd	Unnamed Creek	C0701006	Lima	9/1/2021	2	22/30/55	16/24/37
Warren Rd	Fleming Creek	C0901009	Ann Arbor	11/12/2021	3	23/35/42	20/NN/NN
Bemis Rd	Unnamed Creek	C1433002	Freedom	11/12/2021	3	-	29/44/52
Maple Rd	Unnamed Creek	C1812005	Saline	11/10/2021	4	-	36/55/65
Hartman Rd	Unnamed Creek	C1812006	Saline	11/10/2021	2	-	10/NN/NN

GREAT LAKES ENGINEERING GROUP

Washtenaw County (<20' Inspection)

- Culvert naming convention – Example is C0115003
 - Structure number starts with C for culvert
 - Each township has a number assigned
 - For example – Salem Township is #1, Northfield Township is #2, Webster Township is #3, etc.
 - Next number is the Section # within the township
 - Last number is the # of the culvert within that section
 - Culvert is also noted by the Facility (road name) and Feature (drain/creek name if one is provided)
 - Latitude and longitude provided for each culvert



GREAT LAKES ENGINEERING GROUP

Washtenaw County (<20' Inspection)


- Culvert replacement process
 - Local route
 - 50/50 split in the cost to replace the culvert between the county and the township
 - As the culvert continues to deteriorate, the more likely the township is willing to replace the culvert
 - Some townships are quicker to fund replacements than others



GREAT LAKES ENGINEERING GROUP

Washtenaw County (<20' Inspection)

- Culvert replacement process
 - Primary route
 - County funds 100% of the replacement for primary route
 - Higher the average daily traffic (ADT) and the worse the condition of the culvert, the more likely the county is willing to replace the culvert



GREAT LAKES ENGINEERING GROUP

Bay County (<20' Inspections)

- Inspection process:
 - Culverts and bridges included in the inspection list have a span that ranges from 10' to 20'
 - Culverts and bridges are inspected at a frequency of 5 years maximum depending on their condition
 - Inspection frequency will increase as the condition of the culvert continues to decrease
 - A culvert or bridge in poor condition or worse, the inspection frequency will increase to 12 months or less if necessary



GREAT LAKES ENGINEERING GROUP

Bay County (<20' Inspections)

- Culvert reporting process:
 - All comments and ratings are entered into a Microsoft Access template for each culvert or bridge and a PDF is created
 - Separate template created for a culvert and a bridge

Structure ID	Facility	Feature	Inv. Proj.
Structure 2019/Prasor	Concrete Rd	Squaw Creek, Branch 1	24
Location	Latitude	Longitude	Shape
20 west of Fraser	N43.3369	W84.0143	Circular
Year	Year Recd.	Culvert Mat.	Ins. Date
2019	2019	2019	11/21/2021
Culvert Dia.	Inspection	Agency/Consultant	
36"	Visual	Kierulff Lakes	

Approach	
1. Surface	5
Chipped 11.5 ft. Curves and rutted over pipe.	
2. Headwall	5
Briar on ends.	
3. Shoulder	5
Gravel - grass shoulders.	

Culvert	
4. Joints	7
Lock joints: 90 degree bend inside. Section joints are wrapped. Spalled rock at some joints.	
5. Inlet	7
None noted.	
6. Pipe	7
CRP with 90 degree bend at south end.	
7. Slope	7
Steep and stable.	
8. Channel (SLA-61)	7
Improved county drain. Tall grass. Slow flow.	
9. Scour	7
Bank bermed.	
10. Culvert Barrier (SLA-62)	7
40' CRP. North 20' poly coated. Bend at south. 2 taps.	

Bay County (<20' Inspections)

- Culvert reporting process
 - All typical photos and additional deterioration photos are entered into a photo log template that was created by GLEG and a PDF is created
 - After all the inspection reports and photo logs are created, the PDFs are compiled together and given to the county



Bay County (<20' Inspections)


- Culvert/bridge naming convention
 - Structure number is created based on the Facility (road name) and the distance from the nearest intersection
 - Example – Amelith10WKraenlein and Bowker30SSchoof
 - Culvert/bridge is also noted by the Facility (road name) and Feature (drain/creek name if one is provided)
 - Latitude and longitude provided for each culvert/bridge



GREAT LAKES ENGINEERING GROUP

Bay County (<20' Inspections)

- Culvert and bridge replacement process
 - Primary routes are prioritized for replacement – County does not want any posted less than 20' culverts/bridges if possible
 - Replacement on primary route will be prioritized by average daily traffic (ADT) and condition of the culvert/bridge



GREAT LAKES ENGINEERING GROUP

Bay County (<20' Inspections)

- Culvert and bridge replacement process
 - Replacement on local route is secondary to the primary routes
 - Replacement on local route will be moved up the priority list as the condition continues to decrease or if the culvert/bridge is closed to all traffic
 - County is replacing two culverts/bridges this year with their own forces



GREAT LAKES ENGINEERING GROUP

Road Commission for Oakland County

- County has roughly 290 culverts with <20' span
- Inventory mainly consists of concrete and steel
- Breakdown of culvert condition
 - 77% of inventory in fair or greater (5 or greater)
 - 15% of inventory in poor (4)
 - 8% of inventory in serious or worse (3 or less)
- Roughly 9% of the culverts are weight restricted



GREAT LAKES ENGINEERING GROUP

Oakland County (<20' Inspections)

- Inspection process:
 - RCOC has inspected culverts since the 1990's
 - Originally used an Excel spreadsheet to manage inspections
 - Around 2017, with the assistance of MDOT, started adding structures to MiBRIDGE
 - Since 2017, RCOC periodically finds "new" culverts, and these have been added to MiBRIDGE
 - Currently, MDOT limits structures in MiBRIDGE to a minimum span length of 10 ft.
 - Inspections are grouped by Township



GREAT LAKES ENGINEERING GROUP

Oakland County (<20' Inspections)

- Culvert reporting process:
 - MiBRIDGE is now used to manage RCOC's culvert inspections
 - Inspection frequencies vary from 48 months down to 6 months, depending on condition



GREAT LAKES ENGINEERING GROUP

[illegible]

Oakland County (<20' Inspections)

- Culvert replacement process
 - Local route
 - 50/50 split in the cost to replace the culvert between the county and the township.
 - EXCEPTION to this rule is Dead-End Roads. RCOC funds 100% of a culvert replacement on a Dead-End Road (Oakland County has many lakes, and subsequently many Dead-End Roads with large culverts.)



GREAT LAKES ENGINEERING GROUP

Oakland County (<20' Inspections)

- Primary route
 - County funds 100% of the replacement for primary route
 - Higher the average daily traffic (ADT) and the worse the condition of the culvert, the more likely the county is willing to replace the culvert



GREAT LAKES ENGINEERING GROUP

Difficulties of Inspecting Small Culverts

- Conditions vary from one inspection to the next
 - Following two pictures are from previous inspection
 - High water during inspection, minimal amount of deterioration visible



Difficulties of Inspecting Small Culverts

- Conditions vary from one inspection to the next
 - Following two pictures are from current inspection
 - Low water during inspection, numerous holes and buckled portions of the walls
 - Resulted in significant reduction in load posting



Working to Catch This...



GREAT LAKES ENGINEERING GROUP

Before This Happens...



GREAT LAKES ENGINEERING GROUP



The Project is Finished

Questions & Answers



GREAT LAKES ENGINEERING GROUP